

Model 1300FP SERIES

Neck Velocity		400	500	600	700	800	900	1000	1200	1400	1600
6" An .200 Ak .279	CFM	80	100	120	135	155	175	195	235	275	315
	Ps	.006	.010	.014	.018	.023	.030	.037	.054	.073	.096
	NC	<20	<20	<20	<20	<20	20	25	30	35	40
	Throw	1.0	2.0	2.0	2.5	3.0	3.5	4.0	4.5	5.5	6.5
8" An .350 Ak .354	CFM	140	175	210	245	280	315	350	420	490	560
	Ps	.010	.015	.022	.029	.038	.049	.060	.086	.117	.150
	NC	<20	<20	<20	20	25	30	30	35	40	45
	Throw	2.5	3.5	4.0	4.5	5.0	5.5	6.0	7.0	8.0	9.0
10" An .540 Ak .400	CFM	220	275	325	380	435	490	545	655	765	875
	Ps	.014	.021	.030	.041	.054	.068	.084	.122	.167	.212
	NC	<20	<20	<20	20	25	30	35	40	45	50
	Throw	4.0	5.5	6.5	8.0	9.0	10.5	11.5	14.5	17.0	20.0
12" An .780 Ak .397	CFM	315	395	470	550	630	705	785	945	1100	1260
	Ps	.015	.023	.033	.045	.060	.072	.094	.132	.180	.230
	NC	<20	<20	20	25	30	35	35	40	45	50
	Throw	5.5	7.0	8.5	10.0	11.5	13.0	14.5	17.5	20.5	24.0
14" An 1.070 Ak .393	CFM	430	535	640	750	855	960	1070	1280	1500	1710
	Ps	.023	.036	.051	.071	.093	.115	.140	.205	.277	.350
	NC	<20	<20	25	30	35	35	40	45	50	55
	Throw	7.0	8.5	10.5	12.0	13.5	15.5	17.0	20.5	24.0	24.5

Terminal Velocity of 75 FPM

An = Neck Area in Sq. Ft.

NC = Noise Criteria based on 10dB room absorption (Re: 10^{-12} watts).